

Whicam Story3 CS

Enjoy Wireless & Auto Focus!











Wireless Autofocus Intraoral Camera with Mouse



Enjoy Wireless & Auto Focus!

Wireless Autofocus Intraoral Camera with Mouse

1 Features of Whicam Story3 CS

-  **High speed digital wireless**
High speed digital wireless provide more clear live image without interruption.
-  **Auto focus**
Real Autofocus function shows clear images.
-  **HD image**
High definition show more detail images.
-  **Gyro mouse built-in**
Useable as a mouse.
-  **Adjustable head angle**
User can use the camera with prefer angle.
-  **280° twist head**
Easy to get approach anywhere in oral cavity.
-  **Big capacity battery**
Long time use with big capacity battery.
-  **Software compatibility**
Support keyboard short-cut data changing program and twain driver.
-  **OLED screen**
Bright and clear OLED screen indicates various device status.
-  **Adjustable LED brightness**
Can adjust LED brightness to avoid light reflecting.



2 Wireless receiver

- **USB power operation**
It doesn't need other electric power supply.
The receiver works with USB electric power only.
- **Compact design**
Compact receiver saves space.
- **Unlimited receiver channel**
Digital wireless type support unlimited channel.
User can use many receivers with on camera

4 Minimum System Requirement

PC system:	2.0 Ghz CPU, 1GB RAM
OS:	Windows XP service pack 2 (Windows XP 64 bit is not supported)
USB port:	USB 2.0

3 Specification

Camera (included head)	Operation voltage	3.7V
	Measurement	Approx. 266 x 31 x 37 mm
	Weight	Approx. 140g
	Resolution	1.3 Mega pixel
Charger	Sensor/Lens type	CMOS / Liquid lens
	Measurement	Approx. 169 x 148 x 89 mm
	Weight	Approx. 170 g
Disposable cover	Operation voltage	5V
	Dimensions	Approx. 32 x 100 mm
	Quantity	Approx. 100 pcs by weight x 2ea
Adapter	Raw material	Polyethylene
	Input voltage	AC 100 ~ 240 V
	Output voltage	DC 5V 2A
	UL number	E333054

5 DrsViewer2

Image Viewer included.

